

1 1/2" AUMINIUM/GJUTJÄRN/SYRAFAST

AOD Tryckluftsdriven membranpump

AOD1.5-ABBB
PUMP 1 1/2" BSPT ATEX (CLAMPED)

- Flöde max 400 l/min
- Tryck max 7,0 bar
- Självsgande max 9,0 m
- Hanterar partiklar och viskösa vätskor



Produktinformation

Lämpliga för syror, olja, lösningsmedel, färg, slam, avloppsvatten m.m.


Price® AOD®-pumpar hanterar nästan allt som kan passera genom ett rör. Kapacitet och tryck kan enkelt regleras från 0 till 100 %. Pumparna kan köras mot stängd ventil utan att skadas. De är okänsliga för torrkörning, är självsgande, explosionssäkra och klarar trögflytande medier som också kan vara slitande eller innehålla stora, fasta partiklar.

AOD-pumparna fordrar ingen smörjning och "Price Stall-Free Design" gör att de alltid startar även vid lågt lufttryck samt har lägre luftförbrukning än liknande pumpar.


Teknisk data

Flöde max	400 l/min
Slagvolym	1300 ml
Tryck max	7 bar
Lufttryck	8,8 bar
Sughöjd torr	6,1 m
Sughöjd våt	6,1 m
Anslutning sugsida	1 1/2" BSP
Anslutning trycksida	1 1/2" BSP
Anslutning luft	NPTF 3/8"
Anslutning ljuddämpare	NPTF 1/2"
Material Membran	Buna-N
Material Pumphus	Aluminium


Material Ventiler	Buna-N
Material Ventilsåten	Buna-N
Temperaturområde från	0 °C
Temperaturområde till	82 °C
Partikelstorlek max	4,7 mm
Viskositet	20000 cSt
Vikt	21,8 kg




MODEL (Dimensions)	Aluminum 2000 L Series	Cast Iron 2000 L Series	Stainless Steel 2000 L Series
SUCTION (Bottom)	inches	inches	inches
DISCHARGE (Top)	inches	inches	inches
A - Total Height	inches	inches	inches
B - Total Depth	inches	inches	inches
C - Total Width	inches	inches	inches
Air Inlet Size	inches	inches	inches
Air Exhaust Size	inches	inches	inches
D - Section	inches	inches	inches
E - Air Inlet	inches	inches	inches
F - Discharge	inches	inches	inches
G - Mounting	inches	inches	inches
H - Mounting	inches	inches	inches



MODEL (Dimensions)	Aluminum 2000 L Series	Stainless Steel 2000 L Series
SUCTION (Bottom)	inches	inches
DISCHARGE (Top)	inches	inches
A - Total Height	inches	inches
B - Total Depth	inches	inches
C - Total Width	inches	inches
Air Inlet Size	inches	inches
Air Exhaust Size	inches	inches
D - Section	inches	inches
E - Air Inlet	inches	inches
F - Discharge	inches	inches
G - Mounting	inches	inches
H - Mounting	inches	inches



MODEL (Dimensions)	Aluminum 2000 L Series	Cast Iron 2000 L Series	Stainless Steel 2000 L Series
SUCTION (Bottom)	inches	inches	inches
DISCHARGE (Top)	inches	inches	inches
A - Total Height	inches	inches	inches
B - Total Depth	inches	inches	inches
C - Total Width	inches	inches	inches
Air Inlet Size	inches	inches	inches
Air Exhaust Size	inches	inches	inches
D - Section	inches	inches	inches
E - Air Inlet	inches	inches	inches
F - Discharge	inches	inches	inches
G - Mounting	inches	inches	inches
H - Mounting	inches	inches	inches



MODEL (Dimensions)	Aluminum 2000 L Series	Stainless Steel 2000 L Series
SUCTION (Bottom)	inches	inches
DISCHARGE (Top)	inches	inches
A - Total Height	inches	inches
B - Total Depth	inches	inches
C - Total Width	inches	inches
Air Inlet Size	inches	inches
Air Exhaust Size	inches	inches
D - Section	inches	inches
E - Air Inlet	inches	inches
F - Discharge	inches	inches
G - Mounting	inches	inches
H - Mounting	inches	inches